

FEATURES

- An inspeXtor Platform Compatible Peripheral Powered by Cisco using PoE (Power over Ethernet) Cabling
- The inspeXtor Platform is a PoE Lighting Management System providing Building Automation and Data Collection
- PoE Systems are Safe and Efficient Low Voltage Platforms

SPECIFICATIONS

- Fixture Agnostic up to 80 Watts
- Internal or Optional Remote Mount
- Engineered to Respond to the MHTi Peripheral Communication Network
- RS485 Protocol
- 0-10V External Driver Control
- Wet or Dry Contact Input
- Automatic Network Discovery
- Ultra High Electrical Conversion Efficiency of 98%
- Supports Optional MHTi Battery Backup
- Features a Dimming Range of 1% to 100%
- Dimensions: 7" x 2.75" x 1.5"
- Operating Temperature 32°F to 104°

PROJECT:

TYPE:

NOTES:

- | | |
|--|--|
| Supply Voltage - 24-56 Vdc | Dimming Transition Time - 0.1 to 25 Seconds |
| Max Output Current - 2.0 Amps | 60 Vdc Surge Protection & Short Circuit Protection |
| Response Time - 0.1 Sec | RJ45 Connection Type |
| Off-Mode Power Consumption - 0.5 Watts | |



- All Products are ETL Listed and Assembled in ISO15000/1 Certified US Facility
- Fixtures carry a limited 5-year Warranty (See Warranty Terms and Conditions)
- Every Product is Quality Tested and Inspected Prior to Shipment
- Proudly Manufactured in the USA

inspeXtor Plant Operations

1961 Richmond Terrace
Staten Island, New York 10302
Tel: (718) 524-4370
Fax: (718) 524-4390

West Coast Operations

2285 Michael Faraday Drive
Suite 10
San Diego, California 92154
Tel: (619) 661-0600



Manufactured in the USA

www.inspeXtor.com

888-511-7780

Rev Date: February 2020